



NOTES:

1. CABLE:IEEE 1394 UL 2725[(30AWG*1P+AL/MY+SPIRAL 100%)*2+ CLEAR MYLAR +BRAID 65%] OD:4.0mm COLOR:CLEAR

2. TESTING:

- a.100%TEST OPEN,SHORT,MISWIRE
- b.CONTACT RESISTANCE:2 ohms MAX
- c.INSULATION RESISTANCE:50M ohms MIN
- d.HI-POT:300VDC/1S

3. ALL MATERIAL ROHS COMPLIANT.

4. Specify Length as Suffix on Part Number in mm.

For Example:

1394-10636-1500 = 1500mm Long IEEE 1394 Cable.

2	PVC	20G	45P PVC CLEAR	
1	IEEE 1394 4P	2 SET	SHELL:NICKEL PLATED PIN:G/F	
NO.	DESCRIPTION	Q'TY:	P/N	REMARKS

TOLERANCE	
LINEAR	ANGLES
X.±	X°±
.X±0.25	.X°±
.XXX±0.05	.XXX°±

GENESIS TECHNOLOGY, INC.
3F 5Bld GeXia 1 nd Park
 Longhua Shenzhen China

APPD: _____ MAT'L: _____
 CHKD: _____ FINISH: _____
 DRWN: _____ Q'TY: _____

TITLE: IEEE 1394 4P TO 4P CABLE ASSY			
PART NO.		1394-10636-XX	
DWG NO.		SC-10636	
	UNITS	SCALE	SHEET
	MM	NONE	1 OF 1
			REV
			A

[A]	ISSUED	AXL	2/6/07	.XX±0.15	.XX°±
REV	ECN NO.	NAME	DATE	.XXX±0.05	.XXX°±