



NOTES:

1. COPPER PLATE TO A THICKNESS OF 0.005'(0.002)
TIN PLATE TO A THICKNESS OF 0.008(.0032)
2. 2° DRAFT RUNNING FROM P/L. TO REDUCE MASS .EXCEPT AS NOTED.
3. ALL CORNERS AND FILLETS UP TO 0.38R(.015R)MAX .EXCEPT AS NOTED.
4. DEMENSIONS APPLY AT PARTING LINE OF POINT NEAREST TO IT .EXCEPT AS NOTED.
5. ALL BURRS AND SHARP EDGES SHALL BE REMOVED.
6. DIMENSIONS APPLY AFTER PLATING
7. GATE VESTIGE (2X) MUST NOT VIOLATE MAX O.D.
8. PART SHALL MEET SOLDERABILITY REQUIREMENTS OF SA SPEC 499402
9. DIMENSION IN PARENTHESSES IN INCHS
10. MATERIAL: ZINC#3.

NO.		DESCRIPTION		Q'TY	MATERIAL	PLATED
VISWAR TECHNOLOGIES						
圖名 NAME		GSK-146M				
圖號 DWG NO						
單位 UNIT	MM	一般公差		±0.2	繪圖 DRAW. BY	AXL
比例 SCALE	NONE	.X		±0.1	校對 CHECKED	
SHEET	1/1	.XXX			審核 APPVL. BY	
		ANGLES				

A	ISSUED	9/13/07'	AXL	
REV	DESCRIPTION	DATE	NAME	ECN NO.