



SMCR- 2X 08 - B K X 0 X 1

- ① ② ③ ④ ⑤ ⑥ ⑦ ⑧

1. CONNECTOR:
SMCR: SMART CARD R/A CONNECTOR
2. TYPE:
25: FEMALE, SMT, WITH RIGHT SWITCH (3.81mm),LENGTH 22.3mm, T=2.90, H=0.75
26: FEMALE, SMT, WITH RIGHT SWITCH (3.81mm),LENGTH 22.3mm, T=2.45, H=0.30
27: FEMALE, SMT, WITH RIGHT SWITCH (3.81mm),LENGTH 22.3mm, T=2.30, H=0.15
28: FEMALE, SMT, WITH RIGHT SWITCH (3.81mm),LENGTH 22.3mm, T=2.20, H=0.05
3. POSITIONS
08: 8 POSITIONS
4. INSULATOR MATERIAL
B: LCP+30%G/F
5. INSULATOR COLOR
K: BLACK
6. CONTACT PLATING
1: GOLD FLASH
2: GOLD 3 u"
5: GOLD 15 u"
7. SHIELD PLATING
0: NONE SHIELD
8. PACKING
T: TRAY
R: TAPE REEL

PART NO.	T	H	Plating
SMCR-2508-BKX0X1	2.90	0.75	gold 1~3u"
SMCR-2608-BKX0X1	2.45	0.30	
SMCR-2708-BKX0X1	2.30	0.15	gold 15u"
SMCR-2808-BKX0X1	2.20	0.05	

NOTES:

1. BASE MATERIAL:
LCP+30% G.F,94LV-0 COLOR BLACK
2. TERMINAL:
MATERIAL: COPPER ALLOY T= 0.20 ±0.02
FINISH: GOLD PLATE ON CONTACT AREA, TIN PLATE ON SOLDER TAIL, NICKEL ON ALL SURFACE.
3. RoHS Compliant

TOLERANCE	
LINEAR	ANGLES
X. ± 0.30	X° ± 1.00°
.X ± 0.20	.X° ± 0.20°
.XX ± 0.10	.XX° ± 0.10°
.XXX ± 0.05	.XXX° ± 0.05°



TITLE: SMT SMART CARD	
LENGTH 22.3 mm TYPE WITH RIGHT SWITCH (3.81mm)	
PART NO. SMCR-2X08-BKX0X1	
DWG NO. GTI08-30297	
UNITS	SCALE
MM	NONE
SHEET	REV
1 OF 1	A

[A]	ISSUED	Vegas	10/25/08
REV	ECN NO.	NAME	DATE